



Offer 351238

BOBST AMBITION 76 A1 from 2020

Folder Gluer

Offer Details

Offer Number	351238
Brand	BOBST
Model	Ambition 76 A1
Manufacturer	BOBST
Condition	Very good
Year	2020
Incoterm	Free Carrier
Cylinders Condition	
Under Power	No
Still in production	No
Test possible	No
Complete and in working condition	Yes
Availability	Immediately
Counter	
Machine number	

<p>Description</p>	<p>CUBE adjusting system Carton board: max 800 g/m² Corrugated flute type: N, E, F Speed: 20 to 300 m/min Inching speed: 20 m/min Box sizes: Straight line "C": 126 to 760 mm Straight line "E": 60 to 800 mm Straight line "L": 60 to 385 Crash-lock bottom "C" (2): 146 to 760 mm Crash-lock bottom "L": 70 to 385 mm FEEDER Total length: 610 mm 6 Feed conveyors with 30 mm wide belt with 4 built-in mechanical vibrators 1 Thickness gauge with lateral and lengthwise setting and upper introduction rollers 1 Additional thickness gauge with lateral and lengthwise setting and upper introduction rollers 2 Side guides in two parts Asymmetrical and adjustable in length Max. pile height: 350 mm. 1 set of rear guides for blank support 1 Motor controlled by frequency variator to drive the feed belts and to put in or out of operation PREBREAKER SECTION total length: 2300 mm. 1 lower left conveyor with 43 mm wide belt 1 Lower right conveyor with 25 mm wide belt 1 Set of upper conveyors with 25 mm wide belts and lifting device 1 Left-hand prebreaker without belt with built-in pressing device Adjustable through eccentric Max. width of the glue flap: 30 mm 1 Reopening guide 1 Right-hand prebreaker with 30 mm belt width Including a system to set the prebreaking angle 1 Lower central supporting guide GLUING UNIT 1 Lower left-hand gluing unit with wheel and double scraper 1 HHS gluing system with 2 nozzles, upgradeable up to 4 1 Removable glue basin 1 Upper guide with pressure roller 1 Refill bottle Additional options installed (with factory no.): A-012 <input type="checkbox"/> Delivery, extended version B-012 <input type="checkbox"/> Device for CRASH-LOCK BOTTOM boxes without prebreaking of 3rd crease B-060 <input type="checkbox"/> Device for sleeves and envelopes EA-015 <input type="checkbox"/> Electric pile vibrator For the rear pile guides. Improves the feeding of blanks which are sticking to each other EA-025 <input type="checkbox"/> Blank suction device EA-030 <input type="checkbox"/> Rotary brushes F-020 <input type="checkbox"/> Long upper right conveyor outlet G-001 <input type="checkbox"/> Minimum folding device G-015 <input type="checkbox"/> Central conveyors J-001 <input type="checkbox"/> Infeed device left and right Infeed device with 30 mm belt width J-010 <input type="checkbox"/> Upper pressure belt J-014 <input type="checkbox"/> Additional upper pressing belt DX-027 <input type="checkbox"/> Glue application system without possibility of quality assurance (maximum machine speed 300 m/min) K-012 <input type="checkbox"/> Flipper ejector KX-012 <input type="checkbox"/> Code reader "Stand-Alone" Xtend series Baumerhhs (maximum machine speed 700 m/min) Dismantled In stock</p>
---------------------------	--

Technical details

<p>Max. blank width</p>	<p>760 mm</p>
--------------------------------	---------------

Min. blank width	126 mm
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request

Images



