Offer 385300

BOBST EXPERTFOLD 110 A2 from 2019

Folder Gluer

Offer Details

Offer Number	385300
Brand	BOBST
Model	ExpertFold 110 A2
Manufacturer	BOBST
Condition	Good
Year	2019
Incoterm	
Cylinders Condition	
Under Power	Yes
Still in production	Yes
Test possible	Yes
Complete and in working condition	Yes
Availability	
Counter	
Machine number	

Description	Feeder:Vacuum feeder (ACCUFEED) with blank alignment, Electric pile vibrator, blank suction device, independent upper roller track Max. blank pile height: 350mm Pre-breaker:For straight-line and crash-lock bottom production, Additional pre-breaker with Leary code reader, adjustable pre-breaking angle, Central conveyor, long outlet conveyor for crash-lock bottom/ double-wall boxes Crash-lock Bottom module:Folding/gluing of standard and reinforced crash-lock bottom boxes, Helical folding guides, suction guides for 4/6 corner flaps, Upper extrusion station fitted Gluing unit:Glue wheel with double scraper, removable glue basin Leary nozzle gluing system: 8 channels, 4 glue guns Glue track width: 3mm Folding section:A2 module: rotary hooks (servo motors), auxiliary folder, flexible folding guides, Speedwave 2 module Folding belts: 2 x 10mm/ 2 x15mm / 2 x 30mm, Minimum folding device from 35m, width Device for pitch regulaton Transfer & Delivery:Motorized transfer section, independent drive Extended delivery: total length 6,535mm, pressure length 4,650mm, belt width 900mm, Automatic pressure system (2 zones), box stream regulator Upper pressure belt (for crash-lock bottom boxes), extending pressing belt Inspection & Ejection:Barcode reader, Leary code reader Flipper ejector for faulty boxes, tracked via HMI Control & Automation:Autoset - Fully automatic format setting (CSM CUBE motorized), CUBE control system (Control Unit Bobst Electronic), 15” color touchscreen Storage of up to 5,000 job settings, formats diagram, Remote control, auxiliary control desks at feeder and delivery, Connect Ready (CR) equipment Crash lock and straight line

Technical details

Air consumption	45 m3/h
Stock range	up to 800 g.m2
Stock corrugated Board	N
Max. open blank width	1100 mm
Min. open blank width	126 mm
Crash-lock bottom box	146
Power comsumption	11 kW
Weight approx	4500 kg
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request