



Offer 383737

GALLUS EM 430 from 2011

Label Flexo

Offer Details

Offer Number	383737
Brand	GALLUS
Model	EM 430
Manufacturer	GALLUS
Condition	Good
Year	2011
Incoterm	
Cylinders Condition	
Under Power	Yes
Still in production	Yes
Test possible	Yes
Complete and in working condition	Yes
Availability	
Counter	
Machine number	

Description	Adhesive-side printing (Delam/Relam) capability on two printing stations CS/Multiweb lamination unit The ability to replace one flexographic section with a screen printing unit Full Cylinder hot stamping unit Teknek web cleaning system Sensotec automatic register control BST Powerscope video inspection system GapMaster die-cutting unit Matrix rewinder UV IST system Inserting – web insertion capability Unwinding unit (BG 01) Unwinding unit with pneumatic elevator Web slitting table with pneumatic pressure Dancer system Electric edge guidance with ultrasonic sensor Optical web end sensor 3" pneumatic mandrel Plywood sensor Web break sensor Infeed section (BG 02) "Infeed" feeding unit mounted on a 610 mm platform Voltage adjustment from 50-1000 N Corona system (BG 57) Corona system 5-10 kV 4 electrodes Web cleaning system (BG 58) TEKNEK system Cleaning of both sides Webs 6 × Standard Flexo Printing Unit 2 × Reverse Flexo Printing Unit (double-sided printing) Screen Printing (BG 68 GEN III) 1 × Screen Printing Unit Report Range 12-26" UV System (BG 38) 8 × UV Lamp IST MBS 6 Exhaust Fan UV/Corona Hot Foil Stamping (BG 56) Hot Foil Stamping Unit Report 9-21" Cold Foil Stamping (BG 78) Cold Foil Stamping Kit Die-cutting section, 1 × 24" GapMaster die-cutting unit t Delivery section BG 10 610 mm platform with double Gearbox BG 07 Outfeed unit with die/machine die Video inspection system (BG 55) BST POWERScope 4000 CCD camera with 12x zoom Strobe lamp 19" monitor 390 mm mounting platform Rewinding section (BG 54) Single-spindle rewinder Integrated elevator Max. roll diameter 1250 mm Banana roller with pressure roller Drive and control BG 09 Drive section with touch panel BG 72 Label counter Software Format correction Additional correction for die-cutters Storage of up to 500 jobs Conversion of inches to mm Cooling 27 kW chiller Automatic register control (BG 27 Sensotec) Web Rail system 14 × starting rails 5 × rails 610 mm 40 × rails 1000 mm Delam / Relam (BG 26) Glue-side printing system (up to 2 colors) Additional guide roller Special roller coating Antistatic (BG 62) Simco control unit 2 × antistatic strips 8 × antistatic brushes Carts Carriage for changing printing units Remote diagnostics Remote control via the Internet HEIRES system Documentation and power supply PL/EN documentation Power supply 400 V Power supply for additional devices 230 V 50 Hz Printing accessories 25 × Anilox, 3 × magnetic cylinders 1x104T, 1x116T, 1x136T, 24 × printing cylinders 8x104T, 8x116T, 8x136T Corona treater
--------------------	---

Technical details

Max. Web width:	435 mm
Min. web width	215 mm
Max.Print width	660 mm
Min. print width	304 mm
Max mechanical Speed	150 m/min.

PRICE: Upon request

Images

Pictures available upon request.