



Offer 382198

KBA-RAPIDA RAPIDA 106-7+LTTL CX ALV2
from 2011

7 Color



Offer Details

Offer Number:	382198
Brand:	KBA-RAPIDA
Model:	Rapida 106-7+LTTL CX ALV2
Manufacturer	KBA-RAPIDA
Condition:	Good
Year:	2011
Incoterm:	
Cylinders Condition:	
Under Power:	Yes
Still in production:	Yes
Test possible:	Yes
Complete and in working condition:	Yes
Availability:	05-2026
Counter:	
Machine number:	
Description:	<p>RAPIDA RA 106 7 LTTL CX ALV2 <>CX package (CX additional package) • Microwave package (MW incl. CX) • Thin stock package 40–80 g/m² (DÜ) • Coating unit (L): 8/11 • Dryer (T): 9/10 • Delivery extension ALV2 – 2400 mm • Machine raised 675 mm (with foundation by customer) • Copy start: 36 mm • Voltage / frequency: 400–420 V ±10% / 50 Hz (EU) • Electrical cabinet cooling (for hot/non air-conditioned pressroom) • Machine documentation language: English • CD with machine documentation / spare parts catalog (German + local language) Feeder (infeed) equipment • Thin stock feeder equipment (40–80 g/m²) • Non-stop automatic for pil logistics (requires 8 bar plant air) (x) • Enlarged compressor for setting pneumatics (if no 8 bar plant air) Non-stop pallets: STRATIS – 10 pcs • Pile logistics system (supplier by others) – x1 • Pile entry on operator side • Kersten high-performance anti-static incl. side blowers + ionization (for thin stock) • Pre-stacker unit Sheet transport / press section • SIS (mark-free feeder / lay system) – NOT for film • Board dust extraction system (for</p>

carton) • Intercom system • Mechanical sheet guiding for heavy board (from 600 g/m²) (CX/FO) • Sheet monitoring in press units (additional to perfecting unit) (CX/FO) • FAPC fully automatic plate change incl. pneumatic plate bending bar Inking & dampening • Boettcher ink & dampening rollers (standard inks) • Inking unit temperature control (installation) • Anti-hickey / waste catcher system (Butzenfänger) • Roller coating for low-alcohol printing (Boettcher) Washing systems • Baldwin washing system (blanket + impression + plate wash) – Standard (GTW + WWE DZW) • KASPER motorized cloth rewind unit incl. supply roll • Wash cloth supply roll: 1 pc • Spare wash cloth spindles (1 clean + 1 dirty per set): 4 sets Coating unit (coater) Chamber doctor blade coater – Harris & Bruno (Qty 2) • Bas anilox specification: 100 l/cm (lightweight aluminum anilox) • Coating plate change • Stainless wash pan for chamber doctor blade Delivery (outfeed) • Suction transfer roller (basic) • Pile logistics (delivery) – prepared (by others) • Non-stop delivery (lowerable) (CX) • Powder sprayer unit: GRAFIX MEGATRONIC-HEP with console control + ionization (Kersten) • Extraction system (ECO) Gallery / platforms • Cross stairs on operator side – 675 mm (Qty 4) • Additional feeder platform – 675 mm • Additional delivery platform – 675 mm (with guard rails) • Stainless hanging shelf on press-unit gallery (1 m wide) Air supply • Air cabinet (multi-stage electronically controlled, air-cooled) • Exhaust hood Cooling / dampening circulation units • Baldwin CombiLiner 852 cooling combination unit (inking + dampening) • Water cooling + glycol chiller up to 38°C • Integrated fine filter Drying (selected) • IR/TL/UV drying system (VariDry KBA): E2+F (ALV2 + delivery) – includes UV Console / automation / quality control • ErgoTronic Professional console (included) • ErgoTronic ACR • QualiTronic Professional <>Grafix Multicontrol<>VARIDAMP alcohol dampening<>CX equipment (additional equipment for cardboard until 1.2 mm)<>Baldwin CombiLiner 852 High Tech cooling device<>Thin-Paper device<>Electromechanical double sheet control<>SIS Sensoric Infeed System<>Non Stop feeder<>Lack Unit (Harris & Bruno)<>GRAFIX 3AX powder sprayer

Technical details

Max paper size	750x1060 mm
Min paper size	340x480 mm
Max speed	18.000 sh/h

PRICE: Upon request

Images

Contact: +49 172-371-8407 Email: dirk@roepa.com