



Offer 377498

**TECNAU UNWINDER 550 from
2018**

Unwinders



Offer Details

Offer Number:	377498
Brand:	TECNAU
Model:	Unwinder 550
Manufacturer	TECNAU
Condition:	Good
Year:	2018
Incoterm:	EX Works
Cylinders Condition:	
Under Power:	Yes
Still in production:	Yes
Test possible:	Yes
Complete and in working condition:	Yes
Availability:	04/2025
Counter:	
Machine number:	
Description:	The Unwinder 550 is the ideal solution for advanced digital printers, feed off-line inserters and all standard finishing applications. It can be used to stack, roll to fold and roll to book. The center-shaft driven Unwinder 550 feeds paper into the printer for continuous operation. The main features of the Unwinder 550 include a

screen display, compatibility with mu
an easy-to-use splice station.<>The Ur
equipped with an optional splice sensor
detects roll junctions and stop the fe
secure the safety of Ink-Jet print head
can also be equipped with a heavy paper
graphic arts applications such as phot
brochures and more.<>Speed max.: 600 1
m/min<>Feeding: Pinfeed or pinless<>Pap
- 140# index, 40 - 250 gsm<>(above 200
kit and subject to application review)
mm - 1320 mm or 4" - 52"<>Roll weight
kg<>Web width: 155 mm - 520 mm or 6"
70, 150, 200 mm or 3", 5", 6"<>Tempera
15 - 27° C<>Acoustics: 65 dB(A)<>Humid
<>Dimensions Length: inc loop: 1420 mm
(71.3") / inc loop and max roll: 2310
1140 mm or 44.9"<>Height: excl. displa
42.75" (49.8")<>Weight: 1587 lb or 720
Gray<>High-speed cutting Cutter c20<>
180 m/min<>Feeding: Pinfeed or pinless
with slit merge<>Paper weight: 10.5# l
- 250 gsm<>(paper dependent, above 200
application review)<>Web width: 140 -
20.5"<>Form length: 89 - 457 mm or 3.5'
height: 950 - 1050 mm or 37.4" - 41.3'
10, 12mm<>Electrical Power: 200 - 240
Hz, 10A<>Consumption: 2250 W (in use)
output: 1500 BTU/h<>Temperature: 50°
C<>Acoustics: 75 dB(A)<>Humidity: 40
Length: 1170 mm or 45" / Width: 1170 mm
excl. display 46" 1170 mm<>Weight: 106
kg<>Colour: Gray<>Transport t20 feeder
connection of c2x cutters to finishing
750 ft/min 228 m/min<>Feeding: Pinfeed
weight: 10# bond - 112# cover, 40 - 30
Coated and uncoated paper<>Web width:
- 20.5"<>Sheet length: 89 - 2500 mm or
99"<>Applications: 1-up, 2-up<>Delive
mm or 37.4" - 41.3"<>Justification: Le

based on web input (Adjustable to support
following devices)<>Temperature: 66 - 70 °C<>Acoustics: ~ 70 dB(A)<>Humidity: relative humidity 40% - 80% limit<>Dimensions: Length 710 mm or 27.5" / Width 1170 mm or 46" / Height 1165 mm or 46" / Depth 200 kg<>Color: Dark Grey

PRICE: Upon request



Contact: +49 172-371-8407 Email: